

Date of issue: 2.09.21 NZ Safety Data Sheet

# 1. Identification of the Substance/Mixture and Supplier.

Product Name: HAARLEM DANISH OIL

Uses: Wood oil

Supplier: SUPREME PAINTS LTD

19 Ford Road Onekawa Napier

New Zealand. 06 650 5879

Telephone: 06 650 5879 Emergency Telephone: 021 389 669 (24 hrs)

#### 2. Hazards Identification.

Hazardous Status: Classified as Hazardous according to the criteria of HSNO.

DG Status: Classified as Dangerous Goods according to NZS5433

HAZARD CLASSIFICATIONS	HAZARD STATEMENTS	GHS Pictogram
Flammable liquids, Cat 3	H226 Flammable liquid and vapour.	<b>®</b>
Aspiration hazard, Cat 1	H304 May be fatal if swallowed and enters airways.	<b>&amp;</b>
Serious eye damage/irritation, Cat 2A	H319 Causes serious eye irritation.	<b></b>

Signal Word:	DANGER

# PREVENTION STATEMENTS

	* · · · · =···=·· · · *
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

## RESPONSE STATEMENTS

	· · · = · · · · ·
P370 + P378	In case of fire: Use foam, carbon dioxide or dry chemical powder for extinction.
P101	If medical advice is needed, have product container or label at hand.
P303 + P361	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin
+ P353	with water/shower.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331	Do NOT induce vomiting.
P305 + P351	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
+ P338	present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.



Date of issue: 2.09.21 NZ Safety Data Sheet

Date of issue: 2.0	)9.21	NZ Safety Data Shee	et	
STORAGE STATE	MENTS			
P403 + P235 Store in a well-ventilated place. Keep cool.				
P405 Store locked up.				
DISPOSAL STATE	MENTS			
P501 D	o not let this prod	duct enter the environment	. Do not dispose of in waterways or sewers.	
D	ispose of this ma	terial and its container as	hazardous waste, via a licensed facility. See	
lo	cal council for di	sposal/recycling informatio	n.	
3. Composit	ion/Information	on Ingredients.		
<b>Chemical Entity</b>		CAS Number	Proportion %w/w	
Tung Oil		8001-20-5	30-60	
Naphtha, petroleur	n, hydrotreated	64742-48-9	30-60	
heavy	•			
Drier blends		Mixture	<1	
Balance of ingredie	ents: Non-hazard	ous, or below the hazardo	us threshold.	
J				
4. First Aid N	Measures.			
Swallowed	If swalle	owed do NOT induce vomi	ting. Give water to drink. Get medical attention if	
		ms occur.		
Inhaled			n air immediately. Begin artificial respiration if	
			edical attention if symptoms occur.	
Eye Contact			veral minutes. Remove contact lenses, if	
			rinsing. If eye irritation persists: Get medical	
		attention.	3 3,4 334 7 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	
Skin Contact	If skin o	or hair contact occurs, remo	ove contaminated clothing and flush skin and	
			cal attention if symptoms occur.	
Further Information			pisons Centre – 0800 POISON (0800 764 766)	
- or a doctor, immediately.				
5. Fire-Fight	ing Measures.			
Suitable extinguis	shing In case	of fire use water corey (fo	g), foam, dry chemical or CO2.	
media	in case	or me, use water spray (10	rg), roam, ary onemical or GOZ.	
Unsuitable	High vo	lume water jet.		
extinguishing me		namo water jet.		
Hazards from the		or if heated a pressure in	crease will occur and the container may burst.	
substance		or ir ricatou, a pressure iri	oroase will occur and the container may burst.	
Hazardous combi	ustion Decom	position products may inclu	ide.	
products		Decomposition products may include: Carbon oxides, Nitrogen oxides, Other noxious substances.		
Special precautio				
fire-fighters			shall be taken involving any personal risk or	
		suitable training.	. S. S. S. Carton in String any personal not of	
Special protective			ate protective equipment and self-contained	
equipment for fire		Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure		
fighters	mode.	is apparatus (CODIT) With	a ian iado piddo oporatod in poditivo proddito	
	Il Release Meas	ures		
o. Addidenta		u. 501		
Personal precauti	ions Wear a	poropriate Personal Protec	ctive Equipment (see section 8). Provide	
. S. Seriai producti		te ventilation.	and Equipment (600 bootion o). I tovido	
Environmental			nd runoff and contact with soil, waterways,	
precautions			evant authorities if the product has caused	
productions		mental pollution (sewers, v		
	CHAILOH	mentai poliution (sewers, v	valor vvays, son or an j.	



Date of issue: 2.09.21	NZ Safety I		
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert dry material and place in an appropriate waste disposal container. If rags are used for clean-up, they must be soaked in water afterwards (self-combustion hazard). Eliminate all ignition sources. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.		
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Eliminate all ignition sources. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.		
7. Handling and Sto	orage.		
Handling	Wear appropriate PPE, and ensure there is adequate ventilation and extraction in the work area. Avoid skin or eye contact, or breathing in the product. Follow precautions listed in section 2 for handling flammable/combustible liquids.		
Storage		tightly closed, in a cool, well-ventilated area, away from ay from heat, sparks and open flame.	
8. Exposure Contro	ol/Personal Protection		
Exposure Standards – n	o NZ WES data		
Engineering Controls	General ventilation and local exhaust should be suitable to keep vapour concentrations minimised. Ventilation equipment should be explosion-proof when operating in flammable zones.		
Personal Protection			
Respiratory	Wear a vapour respirato	r.	
Eyes	Wear chemical goggles.		
Hands	Wear chemical gloves -	PVC, Polychlorpropene or Nitrile.	
Other	Wear overalls or dust co	oat. Use PVC apron when handling large quantities.	
9. Physical and Ch	emical Properties		
PROPERTY		SPECIFICATION	
Physical state		Liquid	
Colour		Yellowish	
Odour		Hydrocarbon odour	
Odour threshold		No data	
рН		No data	
Melting Pt/Freezing Pt		No data	
Initial Boiling Pt and Boiling Range		179-188°C (Naphtha, Petroleum)	
Flash Pt		54°C (Naphtha, Petroleum)	
Upper/Lower Flammability	or Explosive limits	No data	
Vapour pressure		0.07 kPa @ 20°C (Naphtha, Petroleum)	
Vapour Density		No data	
Relative Density		~0.83	
Water Solubility		Not soluble	



Date of issue: 2.09.21 NZ Safety Data Sheet

Partition Coefficient: n-octanol/water	No data
Auto Ignition temperature	No data
Decomposition temperature	No data
Viscosity	No data

## 10. Stability and Reactivity

Stability	The product is stable	
Possibility of	Under normal conditions of storage and use, hazardous reactions will not occur.	
hazardous reactions	Rags soaked with the product may present an auto-ignition hazard.	
Conditions to avoid	Heat, flames	
Incompatible materials	Strong oxidisers, inorganic acids	
Hazardous	Under normal conditions of storage and use, hazardous decomposition products	
decomposition	should not be produced.	
products		

## 11. Toxicological Information

Data sourced from CCID and/or raw material SDSs. Mixture rules applied

Acute Oral Toxicity	Not Classified
Acute Dermal Toxicity	Not Classified
Acute Inhalation Toxicity	Not Classified
Acute Aspiration Toxicity	May be fatal if swallowed and enters airways.
Skin Irritancy/Corrosion	Not Classified
Eye Irritancy/Corrosion	Causes serious eye irritation
Respiratory Sensitisation	Not Classified
Skin Sensitisation	Not Classified
Mutagenic	Not Classified
Carcinogenic	Not Classified
Reproductive/Development	Not Classified
Toxicity	
STOT-SE	Not Classified
STOT-RE	Not Classified

**Toxicity Data** 

# **Product Acute Toxicity Estimate**

ORAL LD50

>2000 mg/kg

DERMAL LD50

>2000 mg/kg

INHALATION LC50 (vapours)

>20 mg/L/4H

## 12. Ecological Information

This product is not classified as Ecotoxic according to the criteria of HSNO.

Data sourced from CCID and/or raw material SDSs

## Toxicity

Product Calculated Aquatic Ecotoxicity - L(E)C50: >100 mg/L

# Persistence & Degradability

No data



Date of issue: 2.09.21 NZ Safety Data Sheet

Mobility	
No data	
Bioaccumulative Potential	
No data	
Ecotoxic Ingredients:	
Ingredient	Classification
Drier blends (insufficient quantity to trigger	Toxic with long lasting effects
ecotoxicity in the product):	

# 13. Disposal Considerations.

Do not let this product enter the environment. Do not dispose of in waterways or sewers. Dispose of this material and its container as hazardous waste, via a licensed facility. See local council for disposal/recycling information.

## 14. Transportation Information.

Regulated for transport Keep separated from foodstuffs

UN Number: 1263
Proper Shipping Name: PAINT
Class: 3
Packing Group: III
Hazchem: 3Y
Marine Pollutant: No



# 15. Regulatory Information.

Group Standard:	HSR002662	
Surface Coatings & Colorants - Flammable		s & Colorants - Flammable
HSNO CONTROLS		
SDS required when any quantity is	present in a work	place.
At least 2 x 4.5kg powder fire exting	uishers required	when >500L is present in a workplace.
Emergency Response Plan and Se	condary Containm	nent required when >10,000L is present in a workplace
Flammable signage required when	>1000L is stored.	
(Flammable Liquid, Cat 3) Hazardous Substances		>500L (closed containers >5L)
Location Compliance Certificate required for:		>1500L (closed containers up to 5L)
		>250L (open containers)
(Flammable Liquid, Cat 3) Hazardous Atmosphere		>100L (closed containers)
Zone required for:		>25L (decanting)
		>5L (open occasionally
		>1L (open containers in continuous use)
Certified Handler		Not Required
Tracking		Not Required



Date of issue: 2.09.21 NZ Safety Data Sheet

This material is not subject to the following agreements:

- Montreal Protocol (Ozone Depleting Substances)
- The Stockholm Convention (Persistent Organic Pollutants)
- The Rotterdam Convention (Prior Informed Consent)

#### All ingredients are on the New Zealand Inventory of Chemicals (NZIoC), or exempt.

Any existing national regulations on the handling of dangerous substances should be observed. Controls for hazardous substances are based upon current knowledge. Where multiple chemicals are stored, controls will need to take into account aggregate quantities. Contact a WorkSafe approved Compliance Certifier for further information and guidance.

#### 16. Other Information.

HSNO = Hazardous Substances and New Organisms Act 1996.

EPA = Environmental Protection Authority

CCID = Chemical Classification and Information Database (EPA)

NZ WES = New Zealand Work Exposure Standard

Date of SDS Preparation: 2 September 2021 Replaces Version Dated: 21 October 2016

The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance of the product.